


Have connected to a server, selected the postgres database, then selected TOOLS/SERVER CONFIGURATION/pg_hba.conf:

Resulting window:

Type	Database	User	IP-Address	Method	Option
<input checked="" type="checkbox"/>	local	all		trust	
<input checked="" type="checkbox"/>	host	all	127.0.0.1/32	trust	
<input checked="" type="checkbox"/>	host	all	::1/128	trust	
<input type="checkbox"/>	local	replication		md5	
<input type="checkbox"/>	host	replication	127.0.0.1/32	md5	
<input type="checkbox"/>	host	replication	::1/128	md5	



Double click on the last blank line to create a new entry and complete the relevant details:

The screenshot shows the Backend Access Configuration Editor with a dialog box titled 'Client Access Configuration' open. The dialog has the following fields:

- Enabled:
- Type: host
- Database: all
- User: all
- IP Address: 192.168.22.0/24
- Method: md5
- Option: (empty)

Save it, and this is the result:

Type	Database	User	IP-Address	Method	Option
<input checked="" type="checkbox"/>	local	all		trust	
<input checked="" type="checkbox"/>	host	all	127.0.0.1/32	trust	
<input checked="" type="checkbox"/>	host	all	::1/128	trust	
<input type="checkbox"/>	local	replication		md5	
<input type="checkbox"/>	host	replication	127.0.0.1/32	md5	
<input type="checkbox"/>	host	replication	::1/128	md5	
<input checked="" type="checkbox"/>	host	all	192.168.22.0/24	md5	

Although the line looks like it is saved, there is not a subsequent blank line after, and when you save the file and the reopen it, your entry is not in the file:

Type	Database	User	IP-Address	Method	Option
<input checked="" type="checkbox"/>	local	all		trust	
<input checked="" type="checkbox"/>	host	all	127.0.0.1/32	trust	
<input checked="" type="checkbox"/>	host	all	::1/128	trust	
<input type="checkbox"/>	local	replication		md5	
<input type="checkbox"/>	host	replication	127.0.0.1/32	md5	
<input type="checkbox"/>	host	replication	::1/128	md5	